

MACHINE SPECIFICATIONS



© Woodstock International, Inc. • Phone: (800) 840-8420 • Web: www.shopfox.biz

MODEL W1712 1-1/2 HP 6" BELT / 12" DISC COMBINATION SANDER

Product Dimensions

Weight..... 145 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 32-1/2 x 16-1/2 x 29-1/2 in.
Footprint (Length x Width)..... 17 x 14 in.

Shipping Dimensions

Type..... Cardboard Box
Content..... Machine
Weight..... 179 lbs.
Length x Width x Height..... 32 x 30 x 21 in.

Electrical

Power Requirement..... 110V, Single-Phase, 60 Hz
Prewired Voltage..... 110V
Full-Load Current Rating..... 10.5A
Minimum Circuit Size..... 15A
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 5 ft.
Power Cord Gauge..... 14 AWG
Plug Included..... Yes
Included Plug Type..... 5-15
Switch Type..... Toggle Safety Switch w/Removable Key

Motors

Main

Horsepower..... 1.5 HP
Phase..... Single-Phase
Amps..... 10.5A
Speed..... 1725 RPM
Type..... TEFC Capacitor-Start Induction
Power Transfer Direct Drive
Bearings..... Shielded & Permanently Lubricated

Main Specifications

Belt Sander Info

Sanding Belt Width.....	6 in.
Sanding Belt Length.....	48 in.
Sanding Belt Speed.....	1066 FPM
Sanding Belt Tilt.....	90 deg.
Table Length.....	12-3/8 in.
Table Width.....	7 in.
Table Thickness.....	1 in.
Table Tilt.....	Left 0, Right 45 deg.
Max Height of Belt in Vertical Position.....	29-1/2 in.
Belt Tension Release Type.....	Quick Release
Platen Type.....	Cast Iron
Platen Length.....	14-1/2 in.
Platen Width.....	6 in.

Disc Sander Info

Disc Diameter.....	12 in.
Disc Speed.....	1725 RPM
Disc Sandpaper Backing Type.....	PSA
Table Length.....	17-5/8 in.
Table Width.....	10 in.
Table Thickness.....	1 in.
Table Tilt.....	Left 0, Right 45 deg.

Construction Materials

Base.....	Sheet Metal
Table.....	Ground Cast Iron
Frame.....	Sheet Metal
Disc.....	Computer Balanced Cast Aluminum
Miter Gauge.....	Die Cast Aluminum/Aluminum Bar
Paint Type/Finish.....	Powder Coated

Other Related Info

Miter Gauge Slot Width.....	3/4 in.
Miter Gauge Slot Height.....	3/8 in.
Number of Dust Ports.....	2
Dust Port Size.....	2, 2-1/2 in.

Other

Country of Origin	Taiwan
Warranty	2 Years
Approximate Assembly & Setup Time	45 Minutes
Serial Number Location	ID Label on Motor
ISO 9001 Factory	Yes
Certified by a Nationally Recognized Testing Laboratory (NRTL)	Yes

Features

Two Precision-Ground Cast-Iron Tables
Quick Change Belt Release
Direct Ball Bearing Drive
Tables Tilt 0-45 Degrees
Heavy-Duty Miter Gauge